

Technical data sheet

Drop-in anchor for multiple fastenings A4

Item number: 3492244



Drop-in anchor for multiple fastening, with internal thread in steel, for the anchoring of, for example, cable tray systems, consoles, steel constructions, etc. in uncracked concrete in indoor and outdoor areas. To knock in with a hammer. With an edge to prevent the anchor from being pulled in. Rustproof and highly corrosion-resistant. The anchor sleeve tightens against the drill hole wall when the internal pin is knocked in, e.g. using the manual firing tool EHS M. Fire-safety tested, fire protection class R 120 according to European Technical Assessment ETA-07/0135 for concrete.



A4 Stainless steel

Master data

| | |
|---------------------|------------------------|
| Item number | 3492244 |
| Type | EA II M 10x40 A4 |
| Description 1 | Drop-in anchor |
| Description 2 | for multiple fastening |
| Manufacturer | OBO |
| Dimension | M10x40 |
| Colour | stainless steel |
| Material | Stainless steel |
| Smallest sales unit | 50 |
| Unit of quantity | Piece |
| Weight | 4.778 kg |
| Weight unit | kg/100 pc. |

Technical data sheet


Drop-in anchor for multiple fastenings A4

Item number: 3492244



Dimensions

| | |
|-------------|-------|
| Length | 40 mm |
| Dimension L | 40 mm |



Technical data

| | |
|------------------------------------|------------------------|
| Version for | Lightning strike |
| Fastening unit | Miscellaneous |
| Drill hole depth | 40 mm |
| Drill hole diameter, min. | 12 mm |
| Screw-in depth, max. | 17 mm |
| Screw-in depth, min. | 10 mm |
| Thread | M10 |
| Thread metric | 10 |
| Thread type | Metric |
| Self-drilling | no |
| Approvals available | yes |
| Permitted load range, tension zone | 3 |
| Suitable for material | Concrete Natural stone |
| Mounting type, anchor, tie | Pre-mounting |