#### **Technical data sheet**

# **UDHOME2** floor socket, with tube body, unequipped, stainless steel

**Item number: 7427097** 



Square installation unit for use in dry and wet-cleaned cavity and screed floors. Installation housing with pre-marked insertion openings for pipes (M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 110 mm, the height-adjustment range +25 mm. Up to two Modul45® sockets can be installed. Up to two modular data sockets (Keystones) can be installed with optional mounting supports.







Stainless steel

#### Master data


7427097
UDHOME2 VT2
Floor socket
with tube body, unequipped
OBO
140x140x110
Stainless steel
1
Piece
297 kg
kg/100 pc.
16,0732 kg CO2e / 1 Piece

### **Technical data sheet**


# **UDHOME2** floor socket, with tube body, unequipped, stainless steel







Length 140 mm Width 140 mm



т.	90	hn	ica	ΙА	ata

Number of mounting boxes  Version for  Cable outlet version  Equipment Floor covering protection frame Floor care Vet Cover version Seal installation option Floor height, max. Floor height, min. Suitable for raised floor installation Suitable for cavity floor installation Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code Vertical load, large area  Lowerable tube body Empty housing no Wet Decorative plate yes  Decorative plate yes  yes  yes  yes  yes  yes  yes  ye		
Cable outlet version Equipment Equipment Floor covering protection frame Floor care Cover version Seal installation option Floor height, max. Floor height, min. Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when unused Protection rating IK code  Lemant Metallation body Empty housing no  Devocrative plate yes  135 mm 110 mm  yes  yes  yes  yes  yes  140 mm  140 mm  IP20  IP45  IP45  IF45  IF4	Number of mounting boxes	0
Equipment Empty housing  Floor covering protection frame Floor care Wet Cover version Decorative plate Seal installation option yes Floor height, max. 135 mm Floor height, min. 110 mm Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care yes Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess no Protection rating (IP) when used Protection rating IK code  Empty housing no  Empty housing no  Het  Wet  Yes  135 mm  110 mm  yes  yes  yes  140 mm  140 mm  140 mm  140 mm  IP20  IP20  IP45  IR10  IR10	Version for	Square
Floor covering protection frame Floor care Cover version Decorative plate Seal installation option Yes Floor height, max. Floor height, min. Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when unused Protection rating IK code  Net Yes  No  No  No  No  No  No  No  No  No  N	Cable outlet version	Lowerable tube body
Floor care Wet Cover version Decorative plate Seal installation option yes Floor height, max. 135 mm Floor height, min. 110 mm Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care yes Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess no Protection rating (IP) when used Protection rating IK code  Wet Decorative plate yes 140 mm  yes  140 mm  141 mm  142 mm  142 mm  144 mm  144 mm  145 mm  140 mm  140 mm  141 mm  142 mm  143 mm  144 mm  144 mm  145 mm  145 mm  146 mm  147 mm  148 mm  149 mm  140 mm  140 mm  140 mm  140 mm  140 mm  140 mm  141 mm  142 mm  143 mm  144 mm  144 mm  144 mm  145 mm  146 mm  147 mm  148 mm  149 mm  140 mm  140 mm  140 mm  140 mm  140 mm  141 mm  142 mm  143 mm  144 mm  144 mm  145 mm  145 mm  146 mm  147 mm  148 mm  149 mm  149 mm  140 mm  140 mm  140 mm  140 mm  141 mm  142 mm  143 mm  144 mm  144 mm  145 mm  146 mm  147 mm  148 mm  149 mm  140 mm  140 mm  140 mm  140 mm  140 mm  140 mm  141 mm  142 mm  143 mm  144 mm  145 mm  146 mm  147 mm  148 mm  1	Equipment	Empty housing
Cover version Decorative plate Seal installation option yes Floor height, max. 135 mm Floor height, min. 110 mm Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care yes Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code  Decorative plate Pess  Decorative plate  Pess  Decorative plate  Pess  Decorative plate  Decorative plate  Pess  Pess  Decorative plate  Pess  Decoration plate  Pess  De	Floor covering protection frame	no
Seal installation option yes Floor height, max. 135 mm Floor height, min. 110 mm Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care yes Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess no Protection rating (IP) when used Protection rating IK code  IK10	Floor care	Wet
Floor height, max.  Floor height, min.  Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code  135 mm 110 mm yes yes yes 140 mm 141 mm 142 mm 142 mm 143 mm 144 mm 144 mm 145 mm 144 mm 145 mm 140 mm 140 mm 140 mm 141 mm 142 mm 143 mm 144 mm 144 mm 145 mm 146 mm 147 mm 148 mm	Cover version	Decorative plate
Floor height, min.  Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code  110 mm  yes  yes  120  yes  140 mm  141 mm  142 mm  143 mm  144 mm  145 mm  146 mm  147 mm  148 mm  149 mm  140 m	Seal installation option	yes
Suitable for raised floor installation Suitable for cavity floor installation Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code  Wes  yes  140 mm  140	Floor height, max.	135 mm
on Suitable for cavity floor installation Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating IK code  Ves  yes  140 mm  141 mm  142 mm  143 mm  144 mm  145 mm  145 mm  145 mm  145 mm  146 mm  147 mm  148 mm  149 mm  140 mm	Floor height, min.	110 mm
Suitable for wet care Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code  yes  yes  140 mm  140 mm  140 mm  140 mm  140 mm  1420  IP20  IP45  IP45		yes
Suitable for underfloor ducts Device support to accept mounting boxes Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code    Vesting the protection of the protection o	Suitable for cavity floor installation	yes
Device support to accept mounting boxes  Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code  IK10	Suitable for wet care	yes
ting boxes  Length of external dimensions Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code  IK10	Suitable for underfloor ducts	yes
Length of installation dimensions With floor covering recess Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code  IK10		no
With floor covering recess no Protection rating (IP) when used IP20 Protection rating (IP) when unused IP45 Protection rating IK code IK10	Length of external dimensions	140 mm
Protection rating (IP) when used Protection rating (IP) when unused Protection rating IK code  IK10	Length of installation dimensions	140 mm
Protection rating (IP) when unused Protection rating IK code  IK10	With floor covering recess	no
sed Protection rating IK code IK10	Protection rating (IP) when used	IP20
n no and a second new part of the second new		IP45
Vertical load, large area to 15,000 N	Protection rating IK code	IK10
	Vertical load, large area	to 15,000 N

### **Technical data sheet**

**UDHOME2** floor socket, with tube body, unequipped, stainless steel

**Item number: 7427097** 



Technical data		
	Vertical load, small area	to 3,000 N
	Opening mechanism	Sash lock