

Technical data sheet

Barrier strip 60

Item number: 6062389



Barrier strip for the BKRS walkable cable tray system. Fastening with truss-head bolts M 6 x 12 in the base perforation.
For widths of 200 mm or more, a barrier strip with a maximum compartment size of 220 mm should be used.
For widths of 500 mm or more, two barrier strips with a maximum compartment size of 220 mm should be used.



St

Steel

FS

Strip galvanized

Master data

Item number	6062389
Type	TSG 60Z BKRS FS
Description 1	Barrier strip
Description 2	Z type, for BKS
Manufacturer	OBO
Dimension	60x1,5x3000
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	95.934 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	2,6811 kg CO2e / 1 Meter

Technical data sheet

Barrier strip 60

Item number: 6062389



Dimensions

Length	3,000 mm
Length	10 ft
Width	35 mm
Height	55 mm
Plate thickness	1.5 mm
Dimension H	55 mm
Dimension L	3,000 mm

Technical data

Version for	Miscellaneous
Fastening type	Screw-on
Fastening perforation (ETIM)	yes
Maintain electrical functions	no
Suitable for mesh cable tray	no
Suitable for cable ladder	no
Suitable for cable tray	yes
Rustproof steel, pickled	no